according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood P

Revision Date: 04.05.2021 Version 6.0 Print Date 04.05.2021

Date of last issue: 24.07.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sika® Pyroplast® Wood P

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Fire protection system, For professional users only.

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Deutschland GmbH

Kornwestheimer Str. 103-107

D-70439 Stuttgart

Telephone : +49 711 8009 0 E-mail address of person : EHS@de.sika.com

responsible for the SDS

1.4 Emergency telephone number

Emergency CONTACT (24-Hour-Number):

GBK GmbH Global Regulatory Compliance +49(0)6132-84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Reproductive toxicity, Category 2 H361f: Suspected of damaging fertility.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

H361f Suspected of damaging fertility.


Precautionary statements : Prevention:

P201 Obtain special instructions before use.

P261 Avoid breathing dust/ fume/ gas/ mist/ va-

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood P



Date of last issue: 24.07.2020

pours/ spray.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response:

vice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P362 + P364 Take off contaminated clothing and wash it

before reuse.

Hazardous components which must be listed on the label:

melamine

2-methyl-2H-isothiazol-3-one (MIT)

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))

Additional Labelling

EUH211

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Contains a biocide in order to protect the product. Active ingredient: mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)), 55965-84-9. Please use treated articles responsibly.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
melamine	108-78-1	Repr. 2; H361f	>= 5 - < 10
	203-615-4		
	01-2119485947-16-		
	XXXX		

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood P

Revision Date: 04.05.2021 Date of last issue: 24.07.2020 Version 6.0 Print Date 04.05.2021

or last issue: 24.07.2020				
titanium dioxide; [in powder form containing 1 % or more of parti- cles with aerodynamic diameter ≤ 10 μm]	13463-67-7 236-675-5 01-2119489379-17- XXXX	Carc. 2; H351	>= 2,5 - < 5	
Phenol, ethoxylated	9004-78-8 500-013-6	Acute Tox. 4; H302	>= 1 - < 2,5	
2-methyl-2H-isothiazol-3-one (MIT)	2682-20-4 220-239-6 01-2120764690-50- XXXX	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1 specific concentration	>= 0,0015 - < 0,0025	

Skin Sens. 1A; H317

>= 0,0015 %

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood P

Revision Date: 04.05.2021 Version 6.0 Print Date 04.05.2021

Date of last issue: 24.07.2020

55965-84-9 mixture of: 5-chloro-2-methyl-4-Acute Tox. 3; H301 < 0.0002 isothiazolin-3-one [EC no. 247-Acute Tox. 2; H330 911-418-6 01-2120764691-48-500-7] and 2-methyl-2H-Acute Tox. 2; H310 isothiazol-3-one [EC no. 220-239-Skin Corr. 1C; H314 XXXX 6] (3:1) (C(M)IT/MIT (3:1)) Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Corr. 1C; H314 >= 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 % Eye Dam. 1; H318 >= 0,6 %

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact Remove contact lenses.

Keep eye wide open while rinsing.

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood P

Version 6.0 Revision Date: 04.05.2021 Print Date 04.05.2021

Date of last issue: 24.07.2020

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms Allergic reactions

See Section 11 for more detailed information on health effects

and symptoms.

Risks : sensitising effects

> May cause an allergic skin reaction. Suspected of damaging fertility.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known

ucts

5.3 Advice for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

for firefighters

Further information Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system.

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood P

Revision Date: 04.05.2021 Version 6.0 Print Date 04.05.2021

Date of last issue: 24.07.2020

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Storage class (TRGS 510) : 10, Combustible liquids


Further information on stor-

age stability

: No decomposition if stored and applied as directed.

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood P



7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	AGW (Inhalable fraction)	10 mg/m3 (Titanium diox- ide)	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
		AGW (Alveolate fraction)	1,25 mg/m3 (Titanium diox- ide)	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor (Type A) and particulate filter

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in par-

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood P

Revision Date: 04.05.2021 Version 6.0 Print Date 04.05.2021

Date of last issue: 24.07.2020



ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

: liquid Physical state

Colour white

Odour slight

Odour Threshold No data available

Hq ca. 8 (20 °C)

Concentration: 100 %

Melting point/range / Freezing : No data available

point

Boiling point/boiling range No data available

> 101 °C Flash point

Method: closed cup

Evaporation rate No data available

Flammability (solid, gas) No data available

Upper explosion limit / Upper :

flammability limit

No data available

Lower explosion limit / Lower : No data available

flammability limit

23 hPa Vapour pressure

Relative vapour density No data available

Density ca. 1,29 g/cm3 (20 °C)

Solubility(ies)

Water solubility soluble

Solubility in other solvents : No data available

Country DE 100000002910

8 / 15

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood P

Revision Date: 04.05.2021 Version 6.0 Print Date 04.05.2021

Date of last issue: 24.07.2020

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : ca. 2.000 mPa.s (20 °C)

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Explosive properties : No data available

Oxidizing properties : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood P

Revision Date: 04.05.2021 Version 6.0 Print Date 04.05.2021

Date of last issue: 24.07.2020

Components:

melamine:

Acute oral toxicity : LD50 Oral (Rat): 3.161 mg/kg

Acute inhalation toxicity : LC50 (Rat): 5,190 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

2-methyl-2H-isothiazol-3-one (MIT):

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-

one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)):

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

Country DE 100000002910 10 / 15

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood P

Revision Date: 04.05.2021 Version 6.0 Print Date 04.05.2021

Date of last issue: 24.07.2020



ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

2-methyl-2H-isothiazol-3-one (MIT):

M-Factor (Acute aquatic tox- : 10

icity)

M-Factor (Chronic aquatic

toxicity)

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-

one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)):

M-Factor (Acute aquatic tox- : 100

icity)

M-Factor (Chronic aquatic

toxicity)

100

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

Country DE 100000002910

11 / 15

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood P

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

: There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : In accordance with the EWC Waste Regulation the classifica-

tion of waste is to be assigned to the jurisdiction of the origin of waste. Therefore, it is not possible to assign a particular

waste identification number.

Completely emptied packagings may be given for recycling. Empty packaging may still contain hazardous residues. Empty packaging should be removed by a licensed waste contractor. Sika has agreed disposal contracts for all packaging which is

brought into circulation in Germany. For further details see www.sika.de

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Country DE 100000002910 12 / 15

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood P

Version 6.0 Revision Date: 04.05.2021 Print Date 04.05.2021

Date of last issue: 24.07.2020

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich

(Number on list 52)

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

REACH - List of substances subject to authorisation

: None of the components are listed

(=> 0.1 %).

Not applicable

(Annex XIV)

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or - exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Water contaminating class

(Germany)

WGK 1 slightly hazardous to water

Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: < 0,01 %

no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: < 0,01 %

Other regulations:

Country DE 100000002910

13 / 15

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood P



Date of last issue: 24.07.2020

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Product is no subject to the Chemicals Prohibition Ordinance.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H310 : Fatal in contact with skin.
H311 : Toxic in contact with skin.

H314 : Causes severe skin burns and eye damage. H317 : May cause an allergic skin reaction.

H318 : Causes serious eye damage.

H330 : Fatal if inhaled.

H351 : Suspected of causing cancer if inhaled.

H361f : Suspected of damaging fertility.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Carc. : Carcinogenicity
Eye Dam. : Serious eye damage
Repr. : Reproductive toxicity
Skin Corr. : Skin corrosion
Skin Sens. : Skin sensitisation

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

DE TRGS 900 / AGW : Time Weighted Average

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood P

Revision Date: 04.05.2021 Version 6.0 Print Date 04.05.2021

Date of last issue: 24.07.2020

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Skin Sens. 1 H317 Calculation method Repr. 2 H361f Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

DE / EN