according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood Top T Neu

Revision Date: 05.05.2021 Version 3.0 Print Date 05.05.2021

Date of last issue: 02.04.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sika® Pyroplast® Wood Top T Neu

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Fire protection system, For professional users only.

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Deutschland GmbH

Kornwestheimer Str. 103-107

D-70439 Stuttgart

Telephone : +49 711 8009 0 E-mail address of person : EHS@de.sika.com

responsible for the SDS

1.4 Emergency telephone number

Emergency CONTACT (24-Hour-Number):

GBK GmbH Global Regulatory Compliance +49(0)6132-84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Reproductive toxicity, Category 1B H360FD: May damage fertility. May damage the

unborn child.

Specific target organ toxicity - single ex-

posure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Cat-

egory 3

H412: Harmful to aquatic life with long lasting ef-

fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word : Danger

Country DE 100000018803

1 / 15

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood Top T Neu

Revision Date: 05.05.2021 Version 3.0 Print Date 05.05.2021

Date of last issue: 02.04.2019

Hazard statements Flammable liquid and vapour. H226

> May cause drowsiness or dizziness. H336

H360FD May damage fertility. May damage the un-

born child.

Harmful to aquatic life with long lasting ef-H412

fects.

Supplemental Hazard

Statements

EUH066

Repeated exposure may cause skin dryness

or cracking.

Precautionary statements **Prevention:**

> P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/ fume/ gas/ mist/ va-

pours/spray.

Wear protective gloves/ protective clothing/ P280

eye protection/ face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical ad-

vice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics dimethyl propylphosphonate

Additional Labelling

EUH208 Contains 4-morpholinecarbaldehyde. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood Top T Neu



Date of last issue: 02.04.2019

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Components	1	1	i e
Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
Hydrocarbons, C9-C10, n-	Not Assigned	Flam. Liq. 3; H226	>= 40 - < 60
alkanes, isoalkanes, cyclics, <2%	927-241-2	STOT SE 3; H336	
aromatics	01-2119471843-32-	Asp. Tox. 1; H304	
	XXXX [corresponding	Aquatic Chronic 3;	
	group CAS 64742-48-	H412	
	91	EUH066	
	-1		
dimethyl propylphosphonate	18755-43-6	Eye Irrit. 2; H319	>= 5 - < 10
	242-555-3	Repr. 1B; H360FD	
	01-2119960157-35-		
	XXXX		
4-morpholinecarbaldehyde	4394-85-8	Skin Sens. 1; H317	< 1
. ,	224-518-3	,	
	01-2119987993-12-		
	XXXX		

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood Top T Neu

Revision Date: 05.05.2021 Version 3.0 Print Date 05.05.2021

Date of last issue: 02.04.2019

4.2 Most important symptoms and effects, both acute and delayed

Symptoms Erythema

> Loss of balance Vertigo

See Section 11 for more detailed information on health effects

and symptoms.

Risks toxic effects for reproduction

May cause drowsiness or dizziness.

May damage fertility. May damage the unborn child. Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

Water

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Do not use a solid water stream as it may scatter and spread

fire

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

> Remove all sources of ignition. Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentra-


tions. Vapours can accumulate in low areas.

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood Top T Neu

Revision Date: 05.05.2021 Version 3.0 Print Date 05.05.2021

Date of last issue: 02.04.2019



6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Pregnant women or women of child-bearing age should not be

exposed to this product.

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Use explosion-proof equipment. Keep away from heat/ sparks/

open flames/ hot surfaces. No smoking. Take precautionary

measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities


Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood Top T Neu



Date of last issue: 02.04.2019

Storage class (TRGS 510) : 3, Flammable liquids

Further information on stor-

age stability

: No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *	
Hydrocarbons, C9-C10, n-alkanes, isoal-kanes, cyclics, <2% aromatics	Not Assigned	RCP-Group-AGW	226 ppm 1.200 mg/m3	DE TRGS 900	
		AGW	1.500 mg/m3	DE TRGS 900	
	Peak-limit: excursion factor (category): 2;(II)				
	Further information: Group exposure limit for hydrocarbon solvent mixtures, Commission for dangerous substances, See also No. 2.9 of the TRGS 900				
		AGW	300 mg/m3	DE TRGS 900	
	Peak-limit: excursion factor (category): 2;(II)				
	Further information: Group exposure limit for hydrocarbon solvent mixtures				

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	Workers	Skin contact		300 mg/m3 300 mg/kg
	Workers	Inhalation		1500 mg/m3
	Consumers	Skin contact		300 mg/m3 300 mg/kg
	Consumers	Inhalation		900 mg/m3
	Consumers	Ingestion		300 mg/m3 300 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm)

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood Top T Neu

Revision Date: 05.05.2021 Version 3.0 Print Date 05.05.2021

Date of last issue: 02.04.2019

Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor (Type A) and particulate filter

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : various

Odour : aromatic

Odour Threshold : No data available

pH : Not applicable substance/mixture is non-soluble (in water)

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

Flash point : ca. 30 °C

Method: closed cup

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood Top T Neu

Revision Date: 05.05.2021 Version 3.0 Print Date 05.05.2021

Date of last issue: 02.04.2019

: No data available Evaporation rate

Flammability (solid, gas) : No data available

Upper explosion limit / Upper : 7 %(V)

flammability limit

Lower explosion limit / Lower : 0,6 %(V)

flammability limit

Vapour pressure : 4 hPa

Relative vapour density : No data available

: ca. 0,89 g/cm3 (20 °C) Density

Solubility(ies)

: insoluble Water solubility

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : 255 °C

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : ca. 400 mPa.s (20 °C)

Viscosity, kinematic $> 20,5 \text{ mm2/s} (40 ^{\circ}\text{C})$

Explosive properties : No data available

Oxidizing properties : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Country DE 100000018803

8 / 15

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood Top T Neu

Revision Date: 05.05.2021 Version 3.0 Print Date 05.05.2021

Date of last issue: 02.04.2019

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 4.951 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood Top T Neu

Revision Date: 05.05.2021 Version 3.0 Print Date 05.05.2021

Date of last issue: 02.04.2019

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

May damage fertility. May damage the unborn child.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood Top T Neu

Revision Date: 05.05.2021 Version 3.0 Print Date 05.05.2021

Date of last issue: 02.04.2019

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : In accordance with the EWC Waste Regulation the classifica-

tion of waste is to be assigned to the jurisdiction of the origin of waste. Therefore, it is not possible to assign a particular

waste identification number.

Completely emptied packagings may be given for recycling. Empty packaging may still contain hazardous residues. Empty packaging should be removed by a licensed waste contractor. Sika has agreed disposal contracts for all packaging which is

brought into circulation in Germany. For further details see www.sika.de

SECTION 14: Transport information

14.1 UN number

ADR : UN 1263 IMDG : UN 1263 IATA : UN 1263

14.2 UN proper shipping name

ADR : PAINT

(naphtha (petroleum))

IMDG : PAINT

(naphtha (petroleum))

IATA : Paint

(naphtha (petroleum))

14.3 Transport hazard class(es)

Country DE 100000018803

11 / 15

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood Top T Neu

Revision Date: 05.05.2021 Version 3.0 Print Date 05.05.2021

Date of last issue: 02.04.2019

 ADR
 : 3

 IMDG
 : 3

 IATA
 : 3

14.4 Packing group

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen- : 355

ger aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.



according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood Top T Neu

Revision Date: 05.05.2021 Version 3.0 Print Date 05.05.2021

Date of last issue: 02.04.2019

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

: Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

excluded from the regulation, and/orexempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

Water contaminating class

(Germany)

WGK 1 slightly hazardous to water

Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 56,03 %

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 56,03 %

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood Top T Neu



Date of last issue: 02.04.2019

Protection Act - MuSchG).

The product is subject to the supply restrictions of the Ordinance on the Prohibition of Chemi-

cals.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.

H304 : May be fatal if swallowed and enters airways.

H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.
H336 : May cause drowsiness or dizziness.

H360FD : May damage fertility. May damage the unborn child. H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity
Skin Sens. : Skin sensitisation

STOT SE : Specific target organ toxicity - single exposure

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

DE TRGS 900 / RCP-Group-

AGW

DE TRGS 900 / AGW : Time Weighted Average

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road Chemical Abstracts Service

CAS : Chemical Abstracts Ser
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

Calculated according to TRGS 900 RCP-method

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

according to Regulation (EC) No. 1907/2006

Sika® Pyroplast® Wood Top T Neu

Revision Date: 05.05.2021 Version 3.0 Print Date 05.05.2021

Date of last issue: 02.04.2019



and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Flam. Liq. 3 H226 Based on product data or assessment

Repr. 1BH360FDCalculation methodSTOT SE 3H336Calculation methodAquatic Chronic 3H412Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

DE / EN