

Medium Duty Drop Seal




FAS45 40db rated

The recently improved FAS45 Medium Duty Drop Down Seal is an unobtrusive, mortised automatic acoustic and smoke drop seal. It boasts a highly responsive mechanism, ensuring that floor clearance is maintained on opening of the door. The santoprene compression seal gives excellent sealing capabilities against sound, smoke, light and the elements of weather.







SPECIFICATIONS

Test Evidence

- Acoustic: BS EN ISO 10140-2: 2010 (up to Rw 40dB)
- Smoke: BS EN 1634-3: 2004
- Fire: BS 476: Pt 20 and 22: 1987 and BS EN 1634-1: 2014.
- Durability: 1,000,000 Cycles.

Performance

- Meets smoke requirement: BS 9999: 2017.
- Protects against sound, smoke, fire, draught, light and insects.
- > Does not impact accessibility.

Location

- Single swing, single & double leaf doors.
- Designed for use on both right and left handed doors.

Use with

 Can be used with any perimeter seal or threshold plate. Tested alongside our FAS35, FAS35R and FAS39 Perimeter Seals.

Min/max gap size

From 3mm up to 13mm. (Fig.5)

Seal material

Black EPDM rubber.

Standard Lengths

- 400mm, 426mm, 526mm, 610mm,
 626mm, 686mm, 726mm, 762mm,
 826mm, 838mm, 864mm, 914mm,
 926mm, 1026mm, 1200mm, 1300mm.
- Note Each length can be cut back to the next size down. The 400mm can be cut back to 221mm.

\$\$\$\$\$\$\$

Fixing

Fig. 4

Fixing screws are supplied. This seal is mortised. Pre-drilled radiused end plates are supplied which also help to secure the product in place. (Fig. 4)

Adjustment

Self-levelling on uneven surfaces. (Fig. 1)

Finishes

 Silver anodised aluminium with silver end plates and black EDPM rubber gasket.



Issue Number: 1 Issue Date: May 2018

FIRE AND ACOUSTIC SEALS LTD

Units 6 - 11 Spartan Industrial Estate, Brickhouse Lane, West Bromwich, B70 0DH

[t]+44 [0]121 521 2179 [f]+44 [0]121 521 2183 [e] sales@fireandacousticseals.co.uk www.fireandacousticseals.co.uk



Acoustic and Smoke Seals